Safety Data Sheet

1 Material and Supplier Identification

1C270



Product Name:	Super Strip			
Description:	Floor Finish Remover			
Recommended use of the chemical and restrictions:	Use only for the purpose on product label. This product is not intended to be used withour prior dilution if specified on product label.			
Supplier's Information:	Champion Chemical Co. 13300 E. Nelson Ave City of Indusrty, CA 91746 (800) 621-7868 (Customer Service)			
Emergency Telephone:	(800) 255-3924 (Chemtel 24 hrs)			
2 Hazards Identification				
Classification of Mixture:	Serious Eye Damage: Category 1 Skin Corrosion: Category 1B Acute Toxicity Oral: Category 5			
Signal Word:	DANGER			
Hazard Statements:	Causes severe skin burns and eye damage May be harmful if swallowed			
Precautionary Statements				
General:	KEEP OUT OF REACH OF CHILDREN. Read label before use.			
Prevention:	Do not breath vapors. Wash hands thoroughly after handling. Wear protective gloves and eye protection.			
Response:	IF ON SKIN: Take off contaminated clothing and wash before reuse. Rinse skin with water. If skin irritation persists: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes.Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If problem persists, call a Poison Center or get medical attention. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical attention immediately.			

3 Composition/Information on Ingredients

Hazardous Ingredients	CAS Number	Concentration Range %
Potassium Hydroxide	1310-58-3	1-10
2- Butoxyethanol	111-76-2	1-10
Sodium Xylene Sulfonate	1300-72-7	1-5
Disodium Metasilicate Pentahydrate	10213-79-3	1.3

4 First Aid Measures	3
Eye Contact:	Flush eyes with water for 15 minutes. Remove contact lenses if any.
Skin Contact:	Contact with concentrate may be an irritant to sensitive skin. If spilt in large areas of skin, rinse immediately with water and remove clothing. Wash skin thoroughly with soap and water.
Inhalation	If discomfort is experienced after prolonged exposure to vapors, move person to fresh air. Get medical attention if irritation persists.
Ingestion:	Get medical attention immediately. Rinse mouth with water. Do NOT induce vomiting. Drink glass of water to dilute product.

5 Firefighting Measures	
Suitable Extinguishing Media:	Water spray, normal foam, dry agent (carbon dioxide, dry chemical powder.)
Specific Hazards arising from the Chemical:	In a fire or if heated, a pressure increase will occur and the container may burst. Combustion products may include and are not limited to nitrogen oxides, carbon monoxide, and carbon dioxide.
Specific Protective Equipment and Precautions for Firefighters:	Firefighters should wear NIOSH approved self-contained breathing apparatus and protective clothing. If safe to do so, remove containers from path of fire. If involved in a fire, keep containers cool with water spray.

6 Accidental Release Measures

Emergency Procedures:	Keep area clear of personnel until area has been properly cleaned.
Personal Precautions/ Protective Equipment:	Slippery when spilt. To avoid accidents, clean up immediately and shut off source of leak, if safe to do so. Wear appropriate protective equipment to prevent any contamination of skin, eyes, and personal clothing. Provide sufficient ventilation.
Environmental Precautions:	If contamination of sewers or waterways has occurred, advise local emergency services.
Methods for Containment and Cleaning Up:	Contain spill with absorbent (soil, sand, or other inert material) or spill kit to prevent contamination of sewers or waterways. Neutralization agent is not recommended within building, as toxic vapors may be omitted. Properly dispose of used absorbents in accordance with local, state, and federal regulations.

7 Handling and Storage	
Precautions for Safe Handling:	Avoid skin and eye contact, inhalation and ingestion. Wash hands thoroughly after use. Keep out of reach of children.
Conditions for Safe Storage, Including Incompatiibiities:	Store in cool, dry place and out of direct sunlight. Store away from source of heat or ignition. Do not mix with other chemicals. Keep container closed when not in use, and check regularly for leaks.

See Section 10 for incompatible materials.

8 Exposure Controls/Personal Protection			
Control Parameters:			
Hazardous Ingredients	ACGIH TLV	OSHA PEL	NIOSH IDLH
Potassium Hydroxide	N/A	N/A	N/A
2- Butoxyethanol	20 ppm	50 ppm	N/A
Sodium Xylene Sulfonate	N/A	N/A	N/A
Disodium Metasilicate Pentahydrate	N/A	N/A	N/A

Appropriate engineering controls:	Good ventilation should be sufficient to control worker exposure to airborne contaminants.		
Personal Protection			
Eye Protection:	Use protective glasses or safety goggles if splashing or spray-back is likely.		
Hand Protection:	Use protective gloves when used for prolong periods or if skin sensitive.		
Skin Protection:	Use apron if splashing or spray-back is likely.		
Respiratory Protection:	Use in well ventilated areas or local exhaust ventilation when cleaning small spaces.		
Hygiene Measures:	Always wash hands after handling chemical products, and before smoking, eating, drinking, or using the toilet. Wash contaminated clothing or protective equipment before storage and re-use.		

9 Physical and Chemical Properties

Physical State: Color: Odor: pH:	Liquid yellow Lemon 13-14	Specific Gravity: Evaporation Rate: Solubility in Water: VOC (g/L):	1.083 < 1 Complete <70	Vapour Pressure (mm Hg): Vapour Density: Freezing Point (°F): Boiling Point (°F): Flash Point (°F):	< 17 mm Hg > 1 < 32 > 212 > 200
		< means less that	n >n	neans greater than	

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

10 Stability and Reactivity

Reactivity:	No specific data
Chemical Stability:	Stable
Possibility of Hazardous Reactions:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to Avoid:	Avoid exposure to heat and light.
Incompatible Materials:	Slightly reactive or incompatible with oxidizers (e.g., bleach), strong acids (e.g., hydrochloric acid) and reactive metals (e.g., aluminum).
Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 Toxological Information

Symptoms:						
	Eye Contact:	Adverse symptoms may inc	Adverse symptoms may include the following: irritation, watering, redness			
	Skin Contact:	Adverse symptoms may inc	Adverse symptoms may include the following: irritation, redness			
	Inhalation:	Adverse symptoms may inc	Adverse symptoms may include the following: respiratory tract irritation, coughing			
	Ingestion:	Adverse symptoms may inc	Adverse symptoms may include the following: stomach pains			
Acute Toxicity:						
	Eye Contact:	Causes eye irritation				
	Skin Contact:	Causes severe burns.				
	Inhalation:	May cause respiratory irritat	ion.			
	Ingestion:	May cause burns to mouth, throat and stomach.				
Toxicity Data:						
Hazardous Ing		Result	Species	Dose		
Potassium Hydroxide		LD50-Oral	Rat	214 mg/kg		
2- Butoxyethan	ol	LD 50- Derm	al Guinea Pig	>2000 mg/kg		
		LC0 Inhalatic	n Guinea Pig	>3.1 mg/l		
		LC50	Rat, Guinea	13000 mg/kg		
Sodium Xylene	Sulfonate	LD 50- Oral	Rat	>7200 mg/kg		
		LD 50- Derm	al Rabbit	> 2000 mg/kg		
Disodium Metasilicate Pentahydrate		LC50-Inhalat	ion Rat	>206 g/m3		
		LD50-Derma	Rat	>5000 mg/kg		
		LD50-Oral	Rat	1152-1349 mg/kg		
Chronic Effects	5:	No known significant effect	s or critical hazards			

nronic Effects:

12 Ecological Information

Ecotoxicity:

No data available.

Aquatic Toxicity:			
Hazardous Ingredients	Result	<u>Species</u>	Dose
Potassium Hydroxide	LC50	Mosquito Fish	80 mg/l/96 hrs
	LC50	Fathead Minnow	179 mg/l/96 hrs
	EC50	Daphnia magna	60 mg/l/48 hrs
	ErC50	Selenastrum capriconutum	61 mg/L 96 hrs
2- Butoxyethanol	LC 50	rainbow trout	1,474 mg/l/96 hrs
	EC 50	Water Flea	1,550 mg/l/48 hrs
	EbC50	Green Algae	
	IC50	Green Algae	
Sodium Xylene Sulfonate	No Data Availat	ble	
Disodium Metasilicate Pentahydrate	LC50	Brachydanio rerio	210 mg/l 96 hrs
	EC50	Dapnia magna	1700 mg/l 48 hrs
	EC50	Scenedesmus subspicatus	207 mg/l 72 hr(biomass)
	EC50	Scenedesmus subspicatus	>345.4 mg/l 72 hr(growth
rate)			

Other Adverse Effects:

No known significant effects or critical hazards.

13 Disposal Considerations

Disposal Methods:

Diluted product can be flushed to sanitary sewer. Discard empty container in trash. Dispose of waste in accordance with federal, state, and local regulations.

14 Transportation Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes. Ground Transport

5/30/2018	1C270	Super Strip	Page 4 of 5
-----------	-------	-------------	-------------

DOT Classification: UN Number:	Regulated UN1760					
Transport Hazard Class: Packaging Group:	8 II					
Hazardous Division: Corrosive liquids, n.o.s						
Hazardous Contents:	azardous Contents: Potassium Hydroxide					
15 Regulatory Information						
SARA Title III: California Proposition 65: Other Regulations:	Yes No	Contains 2-butc	oxyethanol			
16 Other Information						
HMIS/NFPA Hazard Rating:	Health: 2	Flammability: 1	Reactivity: 0			

The information contained herein is based on the data available to us. It is believed to be correct. NO warranty, expressed or implied, is made regarding the accuracy of this data or the results to be obtained from the use thereof. For further information consult Champion Chemical Co..

SDS Revision Date: 5/30/2018